

EXCAVATOR MOUNTED



SIDE CLAMP VIBRATORY DRIVERS/EXTRACTORS

- Removable side-clamp & Rototilt attachments
- Powered with excavator or MKT hydraulic power unit
- Operate with remote pendant, wireless remote, or joystick controls
- Rotational, side-to-side, fore / aft capabilities for pile plumbing & placement
- Low headroom applications



*** Can be configured from Excavator Mounted to Standard Crane Suspended**

MODEL	* V-2ESC	* V-4ESC	* V-5ESC	V-8ESC
Driving Force	25 tons	40 tons	53 tons	80 tons
Frequency High / Low	1,800 CPM	2,250 / 1,750 CPM	1,700 CPM	2,250 / 1,750 CPM
Eccentric Moment	550 in-lbs	575 in-lbs	1,300 in-lbs	1,150 in-lbs
Amplitude	.50 in	.50 in	.50 in	.50 in
Clamping Force	25 tons	25 tons	62 tons	62 tons
Max. Line Pull Bottom Clamp	16 tons	16 tons	30 tons	32 tons
Max. Line Pull Side Clamp	8 tons	8 tons	15 tons	16 tons
Max. Crowd w/ Side Clamp	8 tons	8 tons	15 tons	16 tons
Weight	5,750 lbs	6,750 lbs	10,750 lbs	9,250 lbs
Operating Pressure	3,000 psi	4,500 psi	3,500 psi	4,500 psi
Flow max. / min.	40 gpm	45 / 35 gpm	90 gpm	80 / 65 gpm
Excavator Size	40,000+ lb	50,000+ lb	80,000+ lb	70,000+ lb
POWER UNIT	HP-74	HP-140	HP-200 L.P.	HP-200 H.P.
Engine HP	74 HP	140 HP	200 HP	200 HP
Operating Speed	2,200 RPM	2,100 RPM	2,150 RPM	2,150 RPM
Hydraulic Pressure	3,000 psi	5,000 psi	3,000 psi	5,000 psi
Length	96 in	120 in	136 in	136 in
Width	44 in	50 in	54 in	54 in
Height	69 in	75 in	90 in	90 in
Weight	2,500 lbs	5,000 lbs	7,100 lbs	7,500 lbs